

Automotive Gas Analyzer

KEG-200/15000ppm

Features

- Portable (compact size, light weight)
- Outstanding accuracy, stability and durability
- Response time of less than 10 seconds
- Stand-by for low power consumption when not in use
- Automatic adjustment of warming up time (2-8 minutes)
- Elegant and simple appearance
- RS232 Interface
- According to ISO 3930 specification



Specification

Measuring item	CO, HC	
Measuring method	CO, HC : NDIR	
Measuring range	HC	0-15,000 ppm
Resolution		1 ppm
Measuring range	CO	0.00-10.00%
Resolution		0.01%
Accuracy	Less than $\pm 2\%$	
Response time	Within 10 sec (more than 90%)	
Warming up time	About 2-8 min	
Sample collecting quality	4-6 L/min	
Power	AC110V / AC220V $\pm 10\%$, 50 / 60 Hz	
Power Consumption	About 50 W	
Operation temperature	0°C - 40°C	
Dimensions	285 (W) x 410 (D) x 155(H) mm	
Packing Dimensions	530 (W) x 430 (D) x 350 (H) mm	
Net weight (Gross weight)	4.5 kg (9.2 lbs.)	
Basic accessories	Probe, Probe hose, Spare fuse, Leak test cap, Spare filter, Operation manual, Power cord,	